

L-Series

Modular Design

Designed to accommodate between 10 and 180 keys (or key sets), the innovative L-Series design allows for starting small and later expanding by adding multiples of 10 key positions (called receptor strips) as required.

Receptor strips are defined as locking or non-locking. Locking receptor strips lock the iFob™ in place restricting access to authorised personnel down to the individual key. Non-locking receptor strips provide a solution for organisations requiring less security but still an audit of key usage. Tri-colour LED's indicate which keys can be taken, which keys are restricted and assist the user with returning the key to the correct location.



Locking Receptor Strip with tri-colour LED's

Extension cabinets can be connected to the L-Series system allowing up to a maximum of 540 keys to be managed from a single control pod.



L-Series system with 2 extension cabinets


The cabinets can be supplied with a clear polycarbonate or metal door, or with no door if specified.

The control pod consists of the user interface which includes the LCD, keypad and card or biometric reader.

PC Software Administration

The L-Series is administered from the user friendly Traka32 Windows software supporting a Microsoft Access or SQL database.

The L-Series can communicate with the Traka32 software using a range of different options including Ethernet, Wireless Ethernet, GPRS, RS485, RS232 and modem.



Multiple systems can be networked together over a Local or Wide Area Network to provide accountability for a **limitless** number of keys administered from multiple PC workstations running the Traka32 software.

User Identification

The L-Series can support any type of access control device required to identify a user to the key system. Supported devices include **RFID proximity readers** from all leading access control manufacturers, **magstripe, barcode** and **biometric technologies** such as **fingerprint, hand, vascular** and **retina** scanners are also supported.



SPECIFICATION

Cabinets Dimensions:	H1920 x W605 x D150 (mm)
Control Pod Dimensions:	H565 x W215 x D150 (mm)
Weight:	100kgs
Power Supply:	Input: AC100-240V Output: DC15V
Battery Backup:	DC12V 3.2Ah (24 hours)
Power Consumption:	30W max
Cabinet Material:	Zintec Steel
Colour Options:	Black MNA03 or Cream RAL1013 powder coated
Door Material:	Clear polycarbonate or metal
Operating Temp:	Ambient. For indoor use only
Mounting:	Wall or cabinet stand mounted
Key Positions:	10-180 (360 double density) Extension cabinets allow up to 540 keys
Receptor Strip Support:	Locking, Non locking, Double Density (20 positions), combination of both - all support Tri-Colour LED's
Users per system:	16,000
Communications:	Ethernet (AES-256 encryption optional), Wireless Ethernet, GPRS, RS485, RS232, Modem
Reader Interface:	Wiegand, Clock/Data ABA Tk2, RS232, TTL, Wiegand Anti pass-back, PIN only
Alarm Interface:	3 x 1A/24V relay contacts for connecting to alarms, access control systems, CCTV etc
Certifications:	CE, FCC, ROHS, UL

Note: - For specific information on the vast array of standard and optional software features available please contact Traka or your supplier.

